

# LM22-L200

## 21.5" HD LCD Monitor



### Technical Specification

#### Model

Model	LM22-L200
-------	-----------

#### System

Diagonal	21.5"(16:9)
Resolution	1920×1080
Backlight	LED
Brightness/Luminance (Standard)	200cd/ m <sup>2</sup>
Contrast	1000:1
Angle of View	170°/160°(vertical/horizontal)
Response Time	5ms

#### Interfaces

Input	Standard	1 HD(support HDCVI, HDTV, AHD, CVBS), 1 VGA, 1 HDMI, 1 BNC, 1 Audio
	Optional	-
Output	Standard	1 HD, Built in speakers
	Optional	-

#### General

Consumption (Standard)	≤30W
Consumption (Standby)	≤0.5W

### Features:

- Industrial level LCD panel, suitable for extensive 7×24 continuous works
- High fidelity digital processing, brilliant and vivid video
- Built in stereo speakers and audio amplifier
- Suitable for every video surveillance and security application: displays HDMI/VGA/BNC input
- Included desk stand is easily removable for standard VESA mounting
- Support HDCVI, HDTV, AHD and CVBS 1080P camera display



Power Supply	AC100~240V (+/-10%), 50/60 Hz
Weight	4.79kg(with base)
Dimensions(no base)	516.60x316.70x51.20mm
Work Environment	Temperature: 0°C~ 40°C
	Humidity: 10%~85%

### Accessory

Standard	VGA cable, power cable, pedestal
Optional	Hanging bracket

Dimensions(mm)

