

DH-PFA105

Mount Adapter



- · Built of aluminum alloy.
- · Matched with particular cameras, beautiful and elegant designed.







Series Overview

The Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Scene

Ideal for mounting cameras, and works in temperatures ranging from $-40\,^{\circ}\text{C}$ to $+60\,^{\circ}\text{C}$ ($-40\,^{\circ}\text{F}$ to $+140\,^{\circ}\text{F}$) and in environments with a relative humidity of less than 90%.

Technical Specification

Structure


Casing Material	Aluminum alloy
Product Dimensions	Φ154.9 mm × 80.5 mm (Φ6.10" × 3.17")
Appearance Color	White
Net Weight	0.26 kg (0.57 lb)
Gross Weight	0.32 kg (0.71 lb)
Load Bearing	1.0 kg (2.20 lb)
Installation	Ceiling mount
Applicable Model	Please see "Camera Accessories Selection"
Packaging Dimensions	192 mm × 200 mm × 98 mm (7.56" × 7.87" × 3.86") (L × W × H)

Environment


Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	<90% (RH)
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10%-90% (RH)
Anti-corrosion Level	Basic Protection

Ordering Information			
Туре	Model	Description	
Camera Mount	DH-PFA105	Mount Adapter	

Installation



Dimensions (mm[inch])



Package Information

- Mount adapter × 1
- M4×10 screw × 3