



### Features

- Modular mechanism design provides flexible product configuration and easy maintenance.
- Option with auto-brightness sensor offers application in day and night.
- Option to built-in touch screen for interactive application.

|                     |   |   |   |
|---------------------|---|---|---|
| Panel               | Cell Type / Glass Surface   | TFT LCD / Black Anti-Glare, low reflection coating          |   |
|                     | Aspect Ratio / Size   | Wide / 17" viewable diagonal area                           |   |
|                     | Active Area / Pixel Pitch   | 381.888(H) x 214.812(V) mm / 0.1989(H) x 0.1989(V) mm       |   |
|                     | Native Resolution / Colors  | 1920(H) x 1080(V) / 262 K                                   |   |
|                     | Brightness / Contrast   | 200cd/m <sup>2</sup> (typ) / 400: 1                         |   |
|                     | Response Time   | ≤ 16 ms   |   |
|                     | Viewing Angle (typical)   | H. 90 ° (- 45° ~ + 45°) , V. 50 °(- 30° ~ + 20°)            |   |
|                     | Light Source  | LED , Long life, 50,000 hrs (typ)                           |   |
| Input Sources       | PC System   | Signal  | Analog RGB (0.7/1.0 V <sub>pp</sub> , 75 ohms)          |
|                     |   | Sync  | Separate Sync, Composite Sync, Sync On Green            |
|                     |   | Frequency   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System  | 2W speaker x 2  |   |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Inlet |   |   |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)          |   |   |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)                            |   |   |
| Power               | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz      |   |   |
| Power Consumption   | Operation / Power Saving  | 22 watt , < 2 watt (Support DPMS)                           |   |
| Operating Condition | Temperature / Humidity  | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |   |
| Storage Condition   | Temperature / Humidity  | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |   |
| Certification       | FCC , CE  |   |   |
| Dimensions          | Physical  | With Base(W x H x D) : TBD                                  |   |
|                     |   | Without Base(W x H x D) : 438.0 x 273.0 x 61.0 (mm)         |   |
|                     | Carton  | W x H x D = TBD   |   |
| Weight              | N.W. / G.W.   | 4.2 Kgs / 5.2 Kgs   |   |
| Container Loaded    | 20ft / 40ft / 40ft HQ   | TBD (Sets , By pallet)                                      |   |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | SunlightReadable         | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |