



Features

- Modular mechanism design provides flexible product configuration and easy maintenance
- Optional built-in touchscreen for interactive application
- Optional with auto brightness sensor offers application in day and night

Panel	Cell Type / Glass Surface	TFTLCD / Back Anti-Glare low reflection coating	
	Aspect Ratio / Size	4:3 / 84" viewable diagonal area	
	Active Area / Pixel Pitch	1704(H) x 1278(V) mm / 0.213(H) x 0.213(V) mm	
	Native Resolution / Colors	800(H) x 600(V) / 262 K	
	Brightness / Contrast	350 cd/m ² (typ) / 600:1	
	Response Time	≤ 30 ms	
	Viewing Angle (typical)	H: 160° (-80° ~ +80°), V: 140° (-70° ~ +70°)	
	Light Source	LED, Longlife 50000hs (typ)	
	Input Sources	PC System	Signal
Sync			Separate Sync, Composite Sync, Sync On Green
Frequency			F _H : 30 - 82Khz, F _V : 50 - 75Hz
Audio System		2W speaker x 2	
Input Terminals	1 x VGA (15 Pin Female D-Sub), 1 x PC Audio (Stereo Headphone Jack), 1 x DC Power Plug		
Convenient Features	Auto Calibration, Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages, VESA Mount Ready (VESA 75x75mm)		
Power	External AC to DC power adapter with universal / Auto Sensing AC 90 to 260V/50/60Hz		
Power Consumption	Operation / Power Saving	16 watt, <2 watt (Support DPM)	
Operating Condition	Temperature / Humidity	0C ~ 50C (32F ~ 122F), 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	-20C ~ 60C (-4F ~ 140F), 10% ~ 90% (no condensation)	
Certification	FCC, CE		
Dimensions	Physical	With Flanges (W x H x D): 218.6 x 175.6 (screw-to-screw) x 60.0 (mm) Without Flanges (W x H x D): 218.6 x 163.6 x 60.0 (mm)	
	Carton	W x H x D = 325 x 330 x 135 (mm)	
Weight	NW / GW	25Kgs / 35Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets, By pallet)	

Options	Touch	Vedio / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage (Sandstone)
	Capacitive touch	SV + AV + A / Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sunlight Readable	Light Sensor
	Protected glass			Auto Dimming