



X-15

For demanding environments with space limitations: a versatile display with hard glass protection and multiple video input options that delivers long-lasting performance.

The X-15 is a durable 15" display that is perfect for any environment where space is at a premium. In busy public environments, the NeoV™ Optical Glass protects the display from incidental damage. The attractive metal casing ensures the durability and strength that allow for secure mounting just about anywhere. With built-in video support and multiple input options, the versatile X-15 opens up an array of display possibilities for any environment.

- > NeoV™ Optical Glass
- > Durable metal casing
- > Swift 4 ms response time
- > Crisp 3000:1 dynamic contrast ratio
- > High 320 cd/m² brightness
- > DVI ready for high quality signal
- > Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- > Auto-adjustment for optimal settings
- > Kensington® security socket
- > VESA standard wall mount
- > Available colours: black, white
- > Rigorous screening of the components for mission-critical 24/7 applications



NeoV™ Optical Glass - The most trusted hard glass protection available.
Only on AG Neovo displays

X-15

Specifications

X-15

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	TFT LCD 15.0" (381 mm) XGA 1024 x 768 0.297 mm 320 cd/m ² (Typical) 3000:1 (DCR) 140°/125° (Typical) 16.7M 4 ms (GTG)
Frequency (H/V)		H: 30 kHz - 60 kHz V: 56 Hz - 75 Hz
Input	Analogue Digital S-Video CVBS	15-Pin D-Sub 24-Pin DVI-D 4-Pin Mini DIN RCA
Power	Power Supply Power Requirements Consumption	External DC 12V < 36 W (on) < 2 W (Stand-by) < 1 W (Off)
NeoV™ Optical Glass	Thickness Reflection Rate Transmission Rate Coating Hardness	3.0 mm (0.12") < 1% > 96% > 9H
Plug & Play	VESA	DCC 2B, DCC/GI
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 90%
Storage Conditions	Temperature Humidity	-20 °C ~ 60 °C 5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	0° ~ +20°
Dimensions	Product (W x H x D) Packaging (W x H x D)	380 x 359 x 155 mm (15.0" x 14.1" x 6.1") 477 x 445 x 217 mm (18.8" x 17.5" x 8.5")
Weight	Product Weight Packaged Product Weight	4.8 kg (10.6 lbs) 7.0 kg (15.4 lbs)
Regulation Approval	Certifications & Compliance	TUV/Bauart, CB, FCC, CE, CCC, CEL, GOST-R, WEEE, RoHS, Vista/Basic, REACH
Accessories	Supplied	CD ROM (user manual and drivers), power cord, power adaptor, 15-Pin D-Sub cable, 24-Pin DVI-D cable, S-Video cable, CVBS cable



Available in black or white



Front-panel keypad with Input Select, Screen Menu, Contrast and Brightness controls for quick adjustments



Wide range of I/O connectors for flexibility and expandability in endoscopic video installations



NeoV™ Optical Glass and durable metal casing for water, dust and scratch resistance

