

INR-100

16-Channel 1-bay Mini Standalone NVR




- 1-bay desktop
- Manage up to 16 cameras or video encoders
- Recording up to 16 channels
- Synchronized playback up to 16 channels
- Export video with RAW, AVI and EXE formats
- Event trigger, response and notification
- Location-based management with eMap
- Mobile Client, Web Client
- 16-channel free license included
- Non-ACTi camera support via licensed Camera Device Pack

PHOTO INDICATION



- | | |
|-----------------|------------------|
| 1 Power Button | 6 Audio Line-out |
| 2 USB 3.0 Port | 7 HDMI Port |
| 3 Display Port | 8 USB 3.0 Port |
| 4 Ethernet Port | 9 DVI Port |
| 5 Serial Plrt | 10 Audio Mic-in |


DIMENSION DIAGRAM



Unit: mm [inch]

SOLUTION ARCHITECTURE

Standalone NVR



Remote User: Administrator / Supervisor / Manager / Security Officer

PRODUCT SPECIFICATION**INR-100****• General**

Full Name	ACTi Standalone Network Video Recorder INR-100
Maximum Number of Clients	1 local, 5 remote
Maximum Number of Video Devices	16 Channels
Maximum Number of POS Devices	16 Channels
Access Control and Network I/O Devices	16 Channels
Free License	16 Channels
Compression	H.265, H.264, MPEG-4, MJPEG
Audio Compression	PCM, G.711
Maximum Camera Resolution	Support all ACTi cameras in all resolutions

• Live View

Display Layout Mode	Local: 1, 3, 4, 5, 6, 8, 9, 10, 12, 16 Remote: 1, 3, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64, Custom
View Manager	An interface to define display layouts and the pre-set cameras within layout in the public or private view
View Patrol	Automatic switch between different views or devices
View Panel	Contains the list of pre-defined views for quick launch
Device Panel	Drag and drop video source from device panel into display layout; display camera status
Digital Zoom	Zoom in/out digitally by mouse scroll wheel or by zoom control buttons
Manual Recording / Snapshot	Instant recording upon mouse click / Instant snapshot upon mouse click or hot key
Event Panel	Display event status upon alarm or upon connection loss or recovery between server and client or when the allocated disk space is full or Point-of-sale (POS), Access control and Network I/O status
Two-way Audio	Audio sound from and to all the audio supported devices; audio broadcast to multiple devices at the same time
Dual Stream Management	Live view of stream 1 or stream 2 of dual stream devices
Instant Playback	Instant playback in live view window
Web Controller	Display and connect to pre-configured embedded website

• e-Map

Layout	Area maps with camera icons, small live view windows; hyperlinked
e-Map Type	Google Maps; Static Map (JPG image)
Setup	Display and connect to pre-configured embedded website e-Map image upload; Google maps settings and preset management; camera positioning; vision angle and pointed direction of camera; view positioning; source positioning; extended devices for Point-of-sale (POS), Access control and Network I/O
PTZ Mode	Mouse PTZ mode to control e-Map video streams

• PTZ

Control	Pan, tilt and zoom controls; speed control; both buttons and overlay controls
Preset Points and Tours	Create preset points; create auto tours between preset points
Number of Preset Points	32
Joystick	USB based joystick supported
Supported Protocols	Auto-detect camera's PTZ protocol. Available protocols: ACTi, Pelco-P, Pelco-D, Dynacolor, Visca

• Recording

Recording Throughput	Maximum total bitrate 300 Mbps
Scheduled Recording	Record video with user defined schedule
Event Recording	Record video when the alarm event is triggered, including the pre-event buffered video clip
Speed Up	Different recording frame rate settings for non-event and triggered event
Manual Recording	Instant recording upon mouse click
Pre-Event Recording	User-defined time period to record before event occurs, and the maximum buffer is 60 seconds (default 5 seconds)
Post-Event Recording	User-defined time period to record after event occurs, and the maximum buffer is 3600 seconds (default 30 seconds)
Multiple Stream Management	Live view of stream 1, stream 2 or stream 3 of multi-stream devices
Recording Frame Rate	Max 480 fps total; Max 30 fps per camera

• Storage

Interface	Serial ATA
Maximum HDD Capacity	10 TB
HDD Bay	1 Disk (disk not included)
System Disk	120G SSD
External Storage	eSATA, iSCSI

• Search & Playback

Recording Search	Search video recordings by time, events (motion, DI, Video Status, Network Status, Manual Recordings, extended device status, event confirm status with invalid or valid), channel, bookmark, notification and listed as clickable time-based thumbnails for full-size view and snapshot download
Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x/16x or frame-by-frame; pause; stop
Synchronized Playback	64 channels
Manual Snapshot	Instant snapshot from playback upon mouse click
Digital Zoom	Zoom in/out digitally by PiP (Picture-in-Picture)
Smart Search	Smart search of recorded video by Motion Detection and Tamper
Video Export	Export video clips in EXE, AVI or RAW format; text overlay and Point-of-sale (POS) transaction data supported

* All specifications are subject to change without notice.

* All brand names and registered trademarks are the property of their respective owners.

www.acti.com



• Event Management

Event Trigger	NVR: Disk full, Disk not found, Disk is available, Schedule service start/stop, Video Push start/stop, CPU limit exceeded Video Device: Video motion detection, Passive IR sensor, External device through digital input, Sound detection, Intelligent event detection, Video Push start/stop, Video loss and Recovery, Network loss and recovery Extended Device: Point-of-sale (POS) status, Network I/O status, Access control allowed/denied, Car park status
Event Response	Pop-up window with live video and event confirmation activation, Switch to hotspot window, Switch to customize view, Command a PTZ device to go to a preset point, Play alert sound, Activate external device through digital output, Execute system command to activate other programs, Upload video or snapshot to FTP server, E-mail notification with snapshots, Push notification
Manual Event	Manually activate external devices through digital output via live view monitor
Event Handling	Define the schedule of event manager

• System

Permission Control	Unlimited number of users, Active Directory, Customizable permissions for user groups, Account lockout, Playback password protected, Password validity period
Language	Multi-language support
Language Import/Export	Possibility to import or export language packs for convenient local language management
Customizable User Interface	Define the layout of user interface for live view and playback
Quick Setup	Configure basic settings of NVR
GPS Position	Manual Setting
Operating System	Win 7 Std. Embedded

• Remote Access

PC Client Program	User interface program (Workstation) with live view, PTZ, playback, e-Map, video push, event management, setup
PC System Requirement	Intel Core 2 Quad 2.4GHz, 4GB RAM
PC Operating System	Windows 7, Windows 8, Windows 10, Windows Server 2008, Windows Server 2012
PC Web Browser	Microsoft Internet Explorer with live view, PTZ, playback, e-Map, video push, event management, setup
Mobile Client Program	Mobile device application (Active Mobile Client) supports live view, PTZ control, video push, event or time based search and playback; Supported devices: iPhone, iPad, iTouch and Android device

• Network

Protocol & Service	IPv4/v6, TCP, UDP, DHCP Client, HTTP, DNS, NTP, RTP, RTSP, SMTP, FTP, ICMP, ARP, UPnP, LDAP (client), iSCSI
Ethernet Port	2, Gigabit Ethernet ports (1000 Base-T), RJ-45 connect

• Hardware

Dimensions (W x H x D)	255 x 88 x 230 mm (10" x 3.46" x 8.46")
Weight	3.2 kg (7.2 lb)
Operating Temperature	0°C~ 40°C (32°F ~ 104°F)
Operating Humidity	10% ~ 85% RH
Power Source / Consumption	AC 100-240V
Approvals	CE (EN 55022 Class B, EN 55024), FCC (Part15 Subpart B Class B), UL (for built-in power adapter)
USB	6 x USB 3.0 ports
Audio Port	Mic-in; Line-out
Display port	1 x Displayport, 1 x DVI, 1 x HDMI
Serial Port	2 x RS-232 ports
Extension Ports	1 x eSATA port

• Integration

Unified Solution	Fully compatible with ACTi cameras, encoders, central management system, TV wall and intelligent video surveillance software
Open Platform Solution	Support ONVIF compliant devices