

ZNR-421

32-Channel 4-Bay Standalone NVR



- 4-Bay Standalone NVR
- Manage up to 32 cameras
- Recording up to 32 channels
- Synchronized playback up to 32 channels
- Mobile Client, Web Client
- 32-channel free license included
- Support ONVIF compliant devices

PRODUCT SPECIFICATION

ZNR-421

• General

Full Name	ACTi Standalone Network Video Recorder ZNR-421
Max. Number of Cameras	32 Channels
Free License	32 Channels
Max. Number of Remote Users	128
Compression	H.265, H.264
Maximun local display resolution	12MP
Operating System	Embedded Linux

• Live View / Playback

Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 960p, 720p, D1, 2CIF, CIF
Synchronized Playback	Up to 16 Channels
Audio Input / Output	1 Channel; RCA / 1 Channel; RCA

• Video / Recording

Recording Throughput	Maximum total bitrate 320 Mbps
Max. Frame Rate vs. Resolution	20 fps at 4072 x 3076; 30 fps at 3840 x 2160; 20 fps at 2688 x 1520; 25 fps at 1920 x 1080; 25 fps at 1280 x 720
Scheduled Recording	Scheduled recording records video according to schedule. A 24x7 recording schedule is enabled by default and may be edited as needed to record video in specified periods only.
Motion Detection Recording	A motion detection alarm occurs if an object inside the detection area moves to a certain extent.
Manual Recording	Instant recording upon mouse click
Multiple Stream Management	Main stream that is intended for scheduled recording and recording triggered by events such as alarm inputs or motion detection alarms. Sub Stream with low resolution video that is intended for local or remote real-time monitoring.

• Storage

Interface	SATA
HDD Bay	4
Capability	Up to 8TB for each disk

• Network

Protocol Service	UPnP, NTP, DHCP, PPPoE
Ethernet Port	Non-PoE: 2 port(s), Ethernet (1000 Base-T), RJ-45 connector

• Hardware

CPU	Hi3536
Weight	3.14kg (6.92 lb)
Dimensions	44 × 440 × 344mm (1.7" × 17.3" × 13.5")
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	10% - 90% RH
Power Source	DC 12V
Power Consumption	12 W (Without HDD)
Digital Input / Output	16; Terminal block / 4; Terminal block
USB	USB 3.0 x 1, USB 2.0 x 2
Audio Port	1; Line-in; 3.5mm phone Jack / 1; Line-out; 3.5mm phone Jack
Display Port	VGA x 1, HDMI x 2
Serial Port	RS-485 x 1
Open Platform Solution	Support ONVIF compliant devices